



accessories supplied



| | |
|--|---|
| Bandwidth | DC to 1.2 GHz (-3 dB) |
| Attenuation Ratio | x10 |
| Accuracy | ±2 % |
| Input Impedance | 1 MΩ, 3 pF |
| Rise Time | 291 ps |
| Input Voltage | ±15 V (DC+peak AC) ±40 V (DC+peak AC) absolute maximum voltage |
| Output Voltage - Swing | ±1,5 V (into 50 Ω load) |
| Output Voltage - Offset (typical) | <±5 mV |
| Adjustable output offset range | -28 mV to +28 mV |
| Output Voltage - Noise (typical) | 0,9 mVrms |
| Output Impedance (typical) | 50 Ω (for using 50 Ω input system oscilloscope) |
| Ambient Operating Temperature | -10 °C to 40 °C |
| Ambient Storage Temperature | -30 °C to 70 °C |
| Ambient Operating Humidity | 0 % to 85 % humidity |
| Ambient Storage Humidity | 0 % to 85 % humidity |
| Power Requirements - Standard | 9 V battery or mains adapter 5 VDC / 200 mA or 9 VDC / 150 mA |
| Power Requirements - Optional | power leads (USB, Probus® or Lemo®) |
| Length of BNC Cable | 120 cm |
| Weight | 200 g |
| Dimensions (L x W x H) | 83 mm x 19 mm x 14 mm |
| Order Number | 12050 |