
ATC-5000NG NextGen ATC/DME Test Set



Prepare for Global ATC Modernization with NextGen test technology

The most important thing we build is trust





ATC-5000NG

Software-driven design allows for field updates for adding new features, capability or modifications due to industry changes

Features

- Generates ATCRBS/Mode S interrogations
- Software defined architecture supports legacy and NextGen transponders
- 10.4 inch touch screen LCD display for operator control
- Can be remotely controlled via GPIB or Ethernet
- Legacy command sets supported:
 - SDX-2000 (option)
 - S-1403DL (future option)
- Support for current standards:
 - ATCRBS/Mode S, DO-181E
 - ADS-B, DO-260, DO-260A, DO-260B
 - UAT, DO-282B (option)

- DME (option)
- Multi-Receiver test capability (option)
- TX/RX data logging capability
- Full diversity testing capability
- Enhanced measurement capabilities
- Supports interrogation tables and block transmissions
- Enhanced single and double interrogation modes
- Contains six transmitters

Applications

Order Number 138156

139311 138157

138159

138158

138223

139310

- Engineering development, certification, manufacturing and service
- Capable of performing most MOPS tests for DO-181E, DO-260, DO-260A, DO-260B, DO-282B



- Replacement for the SDX-2000, ATC-1400A and S-1403DL
- Modern architecture design will support NextGen mandates and future standards changes

Equipment Tested

- Transponders Mode S/ADS-B Out
- ADS-B In Receivers
- UAT Transceivers
- 1090MHz DF18 Emitters (surface vehicles)
- ADS-B In Ground Station Receivers
- ADS-R, TIS-B Ground Station Transmitters
- DMEs

See Product S	pecification She	eet for a more o	letailed specification.

The ATC-5000NG is an RF signal generator/receiver for testing Mode 3/A, C and S transponders. The ATC-5000NG was designed with modern software defined radio technology and is the replacement product for the commercial functionality of the SDX-2000, ATC-1400A and S-1403DL.

Order Number	Description
Standard Accessories	
114114	Keyboard w/ touchpad
62302	Power cord, 110V
64020	Power cord set, 220V
139188	Operations Manual
139189	Getting Started Manual

Dimensions

Size:	10.5"H x 19 26.67 cm x 4	"W x 16.5"D 48.26 cm x 41.9 cm
Weight:	44 lbs.	
Environmental		
Temperature		
Full specified performa	ince	23 ± 5 degrees C
Operating		0 to 45 degrees C
Storage		-30 to 85 degrees C
Relative Humidity		0 to 95% non- condensing

VERSIONS, OPTIONS AND ACCESSORIES

Description
ATC-5000NG Transponder Test Set
ATCNGOPT01 DME Option
ATCNGOPT02 UAT 978MHZ Option
ATCNGOPT03 Multi-receiver Option
ATCNGOPT04 SDX Command Set Comp
ATCNGOPT05 1400/1403 Command Set Comp
ATCNGOPT06 DO-260B MOPS Test Option

For further information please contact:

Cobham AvComm 10200 West York Street Wichita, KS 67215 USA T: (316) 522-4981 F: (316) 522-1360 E: info-test@aeroflex.com

or contact your local Cobham AvComm sales office

