



a TESEQ Company


The MILMEGA Series 2000 Broadband Dual Band Class A Solid State Microwave Amplifier Range

The AS0860 series of solid state power amplifiers follows the MILMEGA tradition for compact, upgradeable microwave power amplifier solutions with field proven reliability. Developed to cover the frequency band 0.8 - 6.0 GHz in two bands (0.8 GHz to 2.5 GHz and 2.5 GHz to 6 GHz), the topology has significant advantages over single band solutions

AS0860-25/25, 25 Watt P1dB 0.8 GHz-6.0 GHz Dual Band Broadband Amplifier

Power 0.8-2.5 GHz	
Psat (min):	30.0 W
Psat (min)	44.7 dBm
P1dB (min):	25.0 W
P1dB (min):	43.9 dBm
Noise figure (max):	6.0 dB
Gain Variation:	± 2 dB
Power 2.5-6.0 GHz	
Psat (min):	30.0 W
Psat (min)	44.7 dBm
P1dB (min):	25.0 W
P1dB (min):	43.9 dBm
Noise figure (max):	8.0 dB

Gain variation:	± 3.0 dB
Harmonic distortion (max):	-20 dBc
Power consumption:	500 W
Primary Power:	85-264 V (50/60 Hz)
RF Input:	Type N female
RF Output:	Type N female
Weight:	34 kg
Size:	6U



Class leading linearity and noise specifications

- Gain variation with temperature <math><0.06\text{ dB}/^\circ\text{C}</math>
- IP3 typically 10 dB> P1 dB
- Harmonics -20 dBc max
- Spurious (max) -70dBc
- Spurious (typical) -80 dBc

Max power

- Unbeatable power density
- Series 2000 will maintain full forward power into any load condition
- Combiner/coupler integration as standard allows samples of incident and reflected power to be measured with virtually no loss
- 100% tested into short and open circuit
- Up to 250 watts in a single 3U unit
- Consistent over greater than octave bandwidths
- Broadband CW power output to 1 kW

High visibility status and power indicators

- Series 2000 incorporate colour led bar graph displays on the front panel giving an indication of incident and reflected power

Other standard features

- Ethernet, USB and RS232 connections allowing "plug and play" simplicity with the most current user interfaces
- All data is measured at 25 °C driven from a 50 R source and driving into a 50 R load
- Input power (for rated output) 5 dBm
- Input power (no damage) 15 dBm
- Input VSWR (impedance 50 R nominal) 2:1 max
- Output VSWR (impedance 50 R nominal) 2:1 typical
- Load VSWR (any phase) is infinite
- Line input frequency 47-65 Hz
- Operating temperature (ambient air) 0 to 40 °C
- Storage temperature -40 to 70 °C.

Built-in protection

- In the event of internal temperature exceeding 70 °C, the amplifier blocks will automatically switch off to avoid damage
- Unit incorporates a rear panel mounted connector for interlock smc-female

Easily rack mounted

- Amplifiers are standard 3U high units and may be combined in rack mounted form to build higher power amplifiers

Bench models

- 3U high units have bench case options

Warranty

- 5 year parts and labour warranty on all Series 2000 amplifiers

Other amplifiers available in the 0.8-6.0 GHz Dual

Band range:

- AS0860-40/25 - 40/25 watt
- AS0860-40/45 - 40/45 watt
- AS0860-75/25 - 75/25 watt
- AS0860-75/45 - 75/45 watt
- AS0860-150/45 - 150/45 watt
- AS0860-150/90 - 150/90 watt



THE QUEEN'S AWARD
FOR INNOVATION
2012

Designers and Manufacturers of High
Power Microwave and RF Amplifiers

