



## **PROFLINE 2115**

# **15 KVA HARMONICS AND FLICKER MEASURING SYSTEM 3-PHASE**



### **System**

ProfLine 2115 is an accurate and flexible 3-phase system designed to measure harmonics and flicker in accordance with IEC 61000-3-2 and IEC 61000-3-3. The system is supplied complete with a stable, accurate, programmable 5 kVA per phase power source. The ProfLine 2115 system is therefore ready to measure and record any harmonics and flicker created by the EUT. A wide range of different AC source systems are available from Teseq, please see ProfLine 2103, 2105, 2130, 2145 datasheets for suitable systems at other powers or for 1-phase operation.

The system is delivered in a suitable 19" rack, fully integrated and ready to use with the supplied PC which has pre-installed software and calibration files.

Measurements are made using precision, no burden, active hall-effect current transformers connected via a dedicated cable to a multichannel fast Data Acquisition Card (DAQ) fitted inside a PC. One voltage and three current measuring channels per phase are used to make simultaneous measurement of both current and voltage. Calculations are made using dedicated Teseq software (WIN 2100) to determine harmonics (classes A-D), inter-harmonics, flicker, dc, dt, dmax, Pst, Plt, inrush current and 24 x dmax.

- **Complete test system for IEC 61000-3-2 and 3-3**
- **Three phase system up to 16 Amps per phase**
- **Power source suitable for testing to immunity standards**

### **Impedance**

Measurement of flicker requires a fixed, stable source impedance as specified in IEC 61000-3-3 ( $0.24 \Omega + j0.15 \Omega$  in each line and  $0.16 \Omega + j0.1 \Omega$  in the neutral). A suitable impedance unit INA 2153 is supplied as part of the system.

### **Power quality measurement**

The power source (NSG 1007-15) supplied as part of the ProfLine 2115 system is able to perform tests in conformance to a number of immunity standards. IEC 61000-4-13 (immunity to harmonics and interharmonics), IEC 61000-4-14 (voltage fluctuations), IEC 61000-4-17 (ripple on DC) and IEC 61000-4-28 (variation of power frequency). Additionally it can also perform pre-compliance testing to IEC 61000-4-29 (voltage dips, interrupts and variations on DC supply) and IEC 61000-4-11. With the addition of further options IEC 61000-4-8 (power frequency magnetics) and fully compliant IEC 61000-4-11 (voltage dips, interrupts and variation on AC supply) can be implemented.

# PROFLINE 2115

## 15 KVA HARMONICS AND FLICKER MEASURING SYSTEM 3-PHASE

### Technical information

Mains supply options	ProfLine 2115-208	ProfLine 2115-400
System contents	NSG 1007-15-208 Power source CCN 1000-3 3-phase Coupling unit DAQ card Interface cable WIN 2100 H&F test software WIN 2110 PQT test software Pre-configured PC USB cable	NSG 1007-15-400 Power source CCN 1000-3 3-phase Coupling unit DAQ card Interface cable WIN 2100 H&F test software WIN 2110 PQT test software Pre-configured PC USB cable
<b>Power source</b> (for full specification see separate datasheet)		
Power output (AC mode)	3 x 5,000 VA	3 x 5,000 VA
Voltage AC, two ranges	0-150 V and 0-300 V	0-150 V and 0-300 V
Maximum current (low range)	37.0 Amps/phase, 110 Amps peak repetitive	37.0 Amps/phase, 110 Amps peak repetitive
Maximum current (high range)	18.5 Amps/phase, 96 Amps peak repetitive	18.5 Amps/phase, 96 Amps peak repetitive
Frequency range (AC mode)	16 – 1000 Hz	16 – 1000 Hz
Power output (DC mode)	3,500 watts/phase	3,500 watts/phase
Voltage DC, two ranges	0-200 V and 0-400 V	0-200 V and 0-400 V
Maximum current (low range)	26.0 Amps	26.0 Amps
Maximum current (high range)	13.0 Amps	13.0 Amps
Supply	3-phase, 208 Vac L-L, 50/60Hz	3-phase, 400 Vac L-L, 50/60Hz
Dimensions (per chassis)	178 x 483 x 610 mm	178 x 483 x 610 mm
Weight (per chassis)	28 kg	28 kg
<b>Coupling unit</b>		
Number of phases	3	3
Measurement channels	4	4
EUT connector: Rear panel	Terminal block	Terminal block
Maximum voltage	300 Vac	300 Vac
Maximum current	40 Arms (200 A Pk for 10 ms)	40 Arms (200 A Pk for 10 ms)
Supply power: Voltage	115/230 Vac +/- 10%	115/230 Vac +/- 10%
Supply power: Current	<0.5 A	<0.5 A
Supply power: Frequency	50/60 Hz	50/60 Hz
Dimensions (HxWxD)	89 x 427 x 560 mm	89 x 427 x 560 mm
Weight	5 kg	5 kg

# PROFLINE 2115

## 15 KVA HARMONICS AND FLICKER MEASURING SYSTEM 3-PHASE

### Technical information

Reference impedance		
Number of phases	3	3
Maximum current per phase (Flicker mode)	37 Amps	37 Amps
Maximum current per phase (ByPass mode)	74 Amps	74 Amps
DAQ card and cable		
Interface	PCI	PCI
Size	Standard height	Standard height
Resolution	16 bit	16 bit
Speed	1.25 MSamples/s	1.25 MSamples/s
Cable length PC to CCN	2 m	2 m
PC	Supplied with DAQ card, card software, WIN 2100, WIN 2110 and system calibration files installed.	
Minimum specifications		
Processor	Pentium 2 GHZ	Pentium 2 GHZ
RAM	2 GB	2 GB
Hard disk	80 GB	80 GB
Operating system	Windows XP or Vista	Windows XP or Vista

### Options

- INA 2196, IEC 61000-3-11, 75 Amps per phase reference impedance
- WIN 2106, test software for IEC 61000-3-11 and IEC 61000-3-12
- Option 8, 1 m magnetic loop antenna 100 A/m continuous and 300 A/m for 3 seconds
- Option 11-3, 3-phase AC switch used to switch power between the source (set to the lower required voltage) and the mains supply in a time between 1-5 us. For details specification please see separate datasheet.
- Avionics immunity & emissions test capability for DO-160, Airbus and Boeing