

Technique parameter

Parameter	IT8211		
Input ratings, (0 ~ 40 °C)	Voltage	0 ~ 60V	
	Current	1mA ~ 30A	
	Power	150W	
Load Regulation	Range	Accuracy	Resolution
	0~10V	±(0.05%+0.1%FS)	1mV
	0~60V	±(0.05%+0.1%FS)	10mV
	0~3A	±(0.1%+0.1%FS)	1mA
	0~30A	±(0.1%+0.15%FS)	10mA
CV Mode Regulation	0.1~60V	±(0.05%+0.1%FS)	10mV
CC Mode Regulation	0~3A	±(0.1%+0.1%FS)	1mA
	0~30A	±(0.1%+0.15%FS)	10mA
CR Mode Regulation (input voltage >= 10%full range, input current >=10%full range)	0.1~10Ω	±(1%+0.8%FS)	0.001Ω
	10~99Ω	±(1%+0.8%FS)	0.01Ω
	100~999Ω	±(1%+0.8%FS)	0.1Ω
	1K~4KΩ	±(1%+0.8%FS)	1Ω
Current Measurement	0~3A	±(0.1% + 0.1%FS)	1mA
	0~30A	±(0.1% + 0.15%FS)	10mA
Voltage Measurement	0~10V	±(0.05% + 0.1%FS)	1mV
	0~60V	±(0.05% + 0.1%FS)	10mV
Power Measurement (input voltage >=10%full range, Input current >=10%full range)	0~10W	±(1%+0.5%FS)	1mW
	10~99W	±(1%+0.5%FS)	10mW
	100~150W	±(1%+0.5%FS)	100mW
Dimension (W*H*D)	88*175*282 (mm)		